AMENDED CLAIMS

- 1.(Currently Amended) A method of thawing meat frozen in meat blocks, comprising providing an apparatus for initial separation of the meat block before the meat block is placed in a rotating container, e h a r act e r i zed in that applying pressure is applied to the meat block (1) before the meat block it is treated in the rotating container (7), said pressure for initiating a separation process of the meat block (1) into individual pieces (2).
- 2.(Currently Amended) The A method according to claim 1, e h a r act e r i zed in that wherein the pressure is applied over the diagonals of the meat block (1).
- 3.(Currently Amended) The A method according to claim 1 or 2, c h a r act e r i zed in that further comprising removing a package is removed from the meat block before the meat block (1) is placed in the rotating container (7).
- 4.(Currently Amended) An apparatus for performing the method, c h a r act e r i zed in that it emprises comprising a number of pistons (3, 4, 5, 6) which either cooperate in pairs or cooperate with a firm opposite face for applying pressure to the meat block (1).
- 5.(Currently Amended) The An apparatus according to claim 4, c h a r act e r i zed in that the faces of wherein the pistons (3, 4, 5, 6) have planar faces facing toward the meat block (1) are plane.
- 6.(Currently Amended) The An apparatus according to claim 4, c h a r act e r i zed in that the faces of wherein the pistons (3, 4, 5, 6) have faces having elevations or depressions facing toward the meat block (1) comprise elevations or depressions.
- 7.(Currently Amended) The An apparatus according to claim 4, c h a r act e r i zed in that the faces of wherein the pistons (3, 4, 5, 6) have an outwardly inclined elevation in at least one corner facing toward the meat block (1) are provided with an outwardly inclined elevation in at least one corner.

8.(Currently Amended) The An apparatus according to claim 4, e h a r act e r i zed in that the faces of wherein the pistons (3, 4, 5, 6) have depressions to receive corners of the meat block (1) facing toward the meat block (1) are provided with depressions to receive the corners of the meat block (1).

9.(Currently Amended) The An apparatus according to claim 4 or 8, c h a r act o r i zed in that wherein the pistons (3, 4, 5, 6) are positioned such that they apply a for applying the pressure to the meat block (1) over the a diagonal or diagonals of the meat block (1).

10.(Currently Amended) The An apparatus according to elaims 4 – 9, c h a r act e r i zed in that it comprises claim 4 further comprising means for detecting and/or removing pieces of metal.